

# Cat<sup>®</sup> CST45 V

## DRIVE SYSTEM

### Specifications

#### Typical Application

Chain Type Longwall Machinery like Armored Face Conveyors (AFC)

#### Maximum Output Torque (for 3 sec) $T_{max}$ [N·m]

KP-45 V CST/P-45 V CST 450 000 N·m 331,858 lb/ft

#### Rated Power P

Ratio i [-]	Rated Power P (n = 1,485 rpm)	Rated Power P (n = 1,782 rpm)
16	1050 kW	1,713 hp
21	1050 kW	1,713 hp
28	1050 kW	1,713 hp
33	1050 kW	1,713 hp
39	820 kW	1,338 hp
45	710 kW	1,158 hp
50	650 kW	1,061 hp

#### Dimensions

##### KP-45 V CST

Length	2875 mm	113.2 in
Width	1401 mm	55.2 in
Height	1060 mm	41.7 in

##### P-45 V CST

Length	1697 mm	66.8 in
Width	1120 mm	44.1 in
Height	1060 mm	41.7 in

#### Capacity

##### KP-45 V CST

Oil Quantity	730 L	193 gal
Gearbox Weight (without oil)	9700 kg	21,380 lb

##### P-45 V CST


Oil Quantity	430 L	114 gal
Gearbox Weight (without oil)	5900 kg	13,000 lb

#### Requirements of Cooling Water

Required Cooling Water Quantity	25 L/min	6.6 gal/min
Maximum Water Inlet Temperature	25° C/298.15 K	77° F/298.15 K

#### Shaft Design

Input Shaft (cylindrical)	DIN 5480-W 120×4
Output Shaft with Internal Toothing	DIN 5480-N 260×10×30×24



GEARBOX RATIO i [-]  
Rated Power P [hp] @ 60 Hz  
Rated Power P [kW] @ 50 Hz

# CST45 V Drive System

---

For more complete information on Cat® products, dealer services, and industry solutions, visit us on the web at [www.cat.com](http://www.cat.com)

AEHQ6878 (02-13)

© 2013 Caterpillar  
All Rights Reserved  
Printed in U.S.A.

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

