

PRODUCT SPECIFICATIONS FOR DE1100 GC

GENERATOR SET SPECIFICATIONS

Minimum Rating	1100 kVA
Maximum Rating	1100 kVA
Emissions/Fuel Strategy	Low Fuel Consumption
Voltage	400 Volts
Frequency	50 Hz
Speed	1500 rpm
Duty Cycle	Standby

ENGINE SPECIFICATIONS

Engine Model	C32 TA, V-12, 4-Stroke Water-Cooled Diesel
Bore	145 mm
Stroke	162 mm
Displacement	32.1 l
Compression Ratio	15.0:1
Aspiration	TA
Fuel System	MEUI
Governor Type	Adem™ A4

GENERATOR SET DIMENSIONS

Length - Minimum	4111 mm
Length - Maximum	4111 mm
Width - Minimum	1823 mm

Width - Maximum	1823 mm
Height - Minimum	2162 mm
Height - Maximum	2162 mm
Dry Weight - Genset (minimum)	6700 kg
Dry Weight - Genset (maximum)	6700 kg

DE1100 GC STANDARD EQUIPMENT

COOLING SYSTEM

Radiator

CONTROL PANEL

GCCP1.3

DE1100 GC OPTIONAL EQUIPMENT

CONTROL PANELS

Remote monitoring software

STARTING/CHARGING

Jacket water heater

GENERAL

Single element or dual element air cleaner,

Circuit breaker panel, based on regional and product configuration