

M315

WHEELED EXCAVATOR



| | |
|--------------------------------------|-----------------------|
| Engine Power (ISO 14396:2002) | 110 kW (148 hp) |
| Maximum Operating Weight | 18 000 kg (39,680 lb) |

Meets U.S. EPA Tier 4 Final and EU Stage V emission standards.



THE NEW CAT® M315

POWERFUL. VERSATILE. COMPACT.

The Cat® M315 Wheeled Excavator provides top performance to get the job done faster. Save time and money with low maintenance costs, longer service intervals, and 100 percent daily ground level maintenance. The compact radius design makes it easy to work in space restricted environments. The M315 gives you the power to work longer while putting money in your pocket.



NEXT GENERATION WHEELED EXCAVATORS


The new line of Cat Wheeled Excavators offers more choices than ever for your business.

- + LOWER OPERATING AND MAINTENANCE COSTS
- + INCREASED OPERATOR EFFICIENCY AND VISIBILITY
- + MORE IN-CAB COMFORT

Ready to help you make your business stronger, Cat Next Generation Wheeled Excavators give you new ways to get the most work done at a cost that fits your business.



DO MORE WORK WITH EXTENDED INTERVALS



* M315F M315

MAXIMIZE PERFORMANCE

Work faster with more swing torque and lower fuel consumption. A smaller front and reduced tail swing radius let you work in space-restricted areas.

UP TO 5%* LOWER MAINTENANCE COSTS

Longer, synchronized service intervals, 100 percent daily ground-level maintenance, and centralized grease points with an autolube option lower your overall costs.

ENHANCED CAB COMFORT

Operate comfortably with the ergonomic control layout and cab options. Get better visibility with rear- and side-view cameras and an optional 360° machine view system.

*Compared to M315F



NEW CAB DESIGN

MAKES HARD WORK EASY

Comfort and movement efficiency help keep you productive and alert all shift long. A tip-up left console lets you get in and out of the cab easily, and the standard seat is wide and adjustable for operators of virtually any size.

POWER MODES

Set and store your power mode preference using Operator ID. Owners can lock in the mode they want their operators to use to help manage fuel consumption.

CUSTOMIZABLE JOYSTICKS

Joystick function can be customized through the monitor. Joystick pattern as well as control response can be set to match operator preference. All preferences are saved with the Operator ID and restored at login.

KEYLESS PUSH TO START

The M315 uses a keyless push-button engine start. This adds security for the machine by using Operator ID codes to limit and track machine access. Codes can be entered manually via an optional Bluetooth® key fob.

TOUCHSCREEN MONITOR

Most machine settings can be controlled through the high resolution 254 mm (10-inch) touchscreen monitor. It offers 42 languages and is easy to read from the seat.

REDUCE OPERATOR FATIGUE

ERGONOMIC LAYOUT

Controls are easy to reach, allowing you to operate comfortably with minimal twists and turns.

REDUCED CAB VIBRATIONS

Work more comfortably with reduced cab vibrations from advanced viscous mounts. The standard ROPS cab meets ISO 12117-2:2008 requirements and helps block outside noise.

BLUETOOTH CONNECTION

Bluetooth-integrated radio allows for seamless mobile phone connection to listen to music, podcasts, and for hands-free calling.

BOOST YOUR PRODUCTIVITY BY UP TO 45%

WITH SIMPLE-TO-USE INTEGRATED CAT TECHNOLOGY



OPTIONAL TECHNOLOGIES INCLUDE:



CAT GRADE WITH 2D

Cat Grade with 2D helps operators reach grade faster. Onboard processors and sensors provide real-time guidance on distance to grade without guesswork. Work safer with fewer ground personnel needed to check the work area for obstacles or grade. All Cat Grade systems are compatible with radios and base stations from Trimble.



CAT PAYLOAD

Onboard weighing system increases loading efficiency with on-the-go weighing. Combine with VisionLink® to manage your production targets remotely (available for download to USB).

Cat Technology gives you the edge. Operators of all experience levels will dig, load and grade with more confidence, speed, and accuracy to save time and money.

CAT TECHNOLOGY MORE WORK, LESS TIME



GET JOBS DONE FASTER WITH LESS REWORK

Cat Grade with Advanced 2D lets you create and edit grade designs with ease on a second high-resolution 240 mm (10 in.) touchscreen monitor. Cat Grade with 3D adds real-time, pinpoint positioning using GPS and GLONASS. Already invested in a grade infrastructure? You can install grade systems from Trimble.

COMPACT RADIUS

SIZED RIGHT FOR CONFINED SPACES

The M315's compact radius design makes it the right machine for working in space-restricted areas. Work confidently in road construction jobs with lane closures and next to buildings and other structures.

The M315 gives you maximum upper frame turning radius, while providing solid lifting performance.



SMARTBOOM™

SmartBoom lets the boom freely travel up and down without using any pump flow, so operators can focus on attachment control and have a smoother cycle.

AUTO AXLE LOCK WITH AUTO BRAKE

The axle locks at zero speed and unlocks when the travel pedal is activated. The axle can also be manually locked with a button on the right-hand console. Auto Axle Brake Lock automatically activates the service brake and locks axle oscillation. It is activated when the travel pedal is in neutral and the machine speed is near zero.

RIDE CONTROL

The ride control system lets you travel faster over rough terrain with improved ride quality. Accumulators act as shock absorbers to help make your journey smoother.

JOYSTICK STEERING

Keep both hands on the joysticks while simultaneously moving the boom and stick and repositioning the machine with the slider switch on the right joystick.



WORK MORE EFFICIENTLY
WITH LESS STRESS

EXPAND YOUR JOBSITE CAPABILITIES

WITH MORE SWING TORQUE AND FUEL EFFICIENCY

An increase in swing torque makes traveling, swinging, and working on slopes easy. Backfill trenches and move around your jobsite faster than before – allowing you to be more productive and finish jobs quickly. An advanced hydraulic system provides the optimum balance of power and efficiency while giving you the control you need for precise digging requirements.





LOWER MAINTENANCE COSTS
UP TO 5%

DO MORE. PAY LESS.

With extended and more synchronized maintenance intervals, you get more done at a lower cost. Consolidated filter locations make service faster.

INFORMATION AT YOUR FINGERTIPS

View operating information such as fuel levels and critical service alerts on the in-cab touchscreen monitor. Your machine's filter life and maintenance intervals are also trackable on the in-cab monitor.

NEW LONGER-LASTING FILTERS

The new hydraulic oil filter provides improved filtration performance, anti-drain valves to keep oil clean when the filter is replaced, and lasts up to 50 percent longer than previous filter designs.

SAFETY FEATURES

LOOK OUT FOR YOUR PEOPLE AND EQUIPMENT



GROUND-LEVEL DAILY MAINTENANCE

All daily maintenance checks can be performed from ground level, making maintenance faster, easier, and safer. Checkpoints include the engine oil dipstick, fuel water separator, fuel tank water and sediment drains, and cooling system coolant level check.

2D E-FENCE

Optional 2D E-Fence is integrated right out of the factory to prevent the excavator from moving outside operator defined set points.

UPPER PLATFORM ACCESS

The service platform design provides easy, safe, and quick access to the upper platform. The steps use anti-skid punch plate to prevent slipping.

SECURE START

Use your PIN code on the monitor or the optional Bluetooth key fob to enable the push-button start feature.

SEE THE JOBSITE AROUND YOU

Enlarged windows and improved machine layout increase visibility from the seat of the cab. Standard rearview and right-side-view cameras always keep operators aware of their surroundings. An optional 360° visibility feature is also available. Powerful, long-lasting LED lights consume minimal power, keeping you safe while working in the dark.

CAT® EQUIPMENT MANAGEMENT TECHNOLOGY TAKES THE GUESSWORK OUT OF MANAGING YOUR EQUIPMENT

Cat Equipment Management telematics technology helps take the complexity out of managing your jobsites by gathering data generated by your equipment, materials, and people and serving it up to you in customizable formats.



PRODUCT LINK™

Product Link™ collects data automatically and accurately from your assets – any type and any brand. Information such as location, hours, fuel usage, productivity, idle time, maintenance alerts, diagnostic codes, and machine health can be viewed online through web and mobile applications.



VISIONLINK®

Access information anytime, anywhere with VisionLink®. Use it to make informed decisions that boost productivity, lower costs, simplify maintenance, and improve safety and security on your jobsite. With different subscription level options, your Cat dealer can help you configure exactly what you need to connect your fleet and manage your business without paying for extras you don't want. Subscriptions are available with cellular or satellite reporting (or both).



Remote Services is a suite of technologies that improves your jobsite efficiency.

Remote Troubleshoot allows your Cat dealer to perform diagnostic testing on your connected machine remotely, pinpointing potential issues while the machine is in operation. Remote Troubleshoot helps ensure the technician arrives with the correct parts and tools the first time, eliminating additional trips to save you time and money.

Remote Flash updates onboard software to potentially reduce update time by as much as 50 percent.

The **Cat App** helps you manage your assets – at any time – right from your smartphone. You can see your fleet location, hours, and other information. You will get critical alerts for required maintenance, and you can even request service from your local Cat dealer.

INCREASE YOUR PRODUCTIVITY AND PROFIT WITH CAT ATTACHMENTS

You can easily expand the performance of your machine by utilizing any of the variety of Cat attachments. Each Cat attachment is designed to fit the weight and horsepower of Cat Wheeled Excavators for improved performance, safety, and stability.

BUCKETS



GRAPPLES



HYDRAULIC HAMMERS



MULCHERS



TILTROTATORS



COMPACTORS



COUPLERS



TECHNICAL SPECIFICATIONS

See cat.com for complete specifications.

| ENGINE | | |
|-------------------------------|----------|-----------------------|
| Engine Model | Cat C4.4 | |
| Engine Power – ISO 14396:2002 | 110 kW | 148 hp |
| Net Power – ISO 9249:2007 | 108 kW | 145 hp |
| Bore | 105 mm | 4.1 in |
| Stroke | 127 mm | 5 in |
| Displacement | 4.4 L | 268.5 in ³ |

- Meets U.S. EPA Tier 4 Final and EU Stage V emission standards.
- Advertised power is tested per the specified standard in effect at the time of manufacture.
- Net power advertised is the power available at the flywheel when engine is equipped with fan, air cleaner, CEM exhaust gas aftertreatment, alternator, and cooling fan running at intermediate speed.
- Recommended for use up to 3000 m (9,843 ft) altitude with engine power derate above 3000 m (9,843 ft).
- Rated speed 2,200 rpm.

| HYDRAULIC SYSTEM | | |
|--|------------|------------|
| Main System – Maximum Flow – Implement | 275 L/min | 73 gal/min |
| Maximum Pressure – Heavy Lift | 37 000 kPa | 5,366 psi |
| Maximum Pressure – Travel | 35 000 kPa | 5,076 psi |
| Maximum Pressure – Normal | 35 000 kPa | 5,076 psi |

| SWING MECHANISM | | |
|----------------------|-----------|---------------|
| Swing Speed | 9.1 rpm | |
| Maximum Swing Torque | 41.3 kN-m | 30,461 lbf-ft |

| WEIGHTS | | |
|--------------------------|-----------|-----------|
| Operating Weight Minimum | 15 700 kg | 34,610 lb |
| Operating Weight Maximum | 18 000 kg | 39,680 lb |

- Operating weight includes full fuel tank, operator, GD bucket and dual pneumatic tires. Weight varies depending on configuration.
- Typical configurations include 2.5 m stick and 4000 kg (8,820 lb) counterweight.

| SERVICE REFILL CAPACITIES | | |
|-----------------------------------|-------|----------|
| Fuel Tank | 280 L | 74.0 gal |
| Diesel Exhaust Fluid (DEF) Tank | 20 L | 5.3 gal |
| Cooling System | 24 L | 6.3 gal |
| Engine Oil | 13 L | 3.4 gal |
| Hydraulic Tank | 90 L | 23.8 gal |
| Hydraulic System (including tank) | 220 L | 58.1 gal |

| TRANSMISSION | | |
|---|----------|------------|
| Forward/Reverse | | |
| 1st Gear | 10 km/h | 6.2 mph |
| 2nd Gear | 35 km/h | 21.7 mph |
| Creeper Speed | | |
| 1st Gear | 5.5 km/h | 3.4 mph |
| 2nd Gear | 15 km/h | 9.3 mph |
| Drawbar Pull | 104 kN | 23,380 Lbf |
| Maximum Gradeability at (16 500 kg/36,376 lb) | 78% | |

| DIMENSIONS | | |
|------------------------------|--|--------|
| Boom | VA 5.2 m (17'1") | |
| Stick | 2.5 m (8'2") | |
| Bucket | GD 0.76 m ³ (0.99 yd ³) | |
| Shipping Height (top of cab) | 3280 mm | 10'9" |
| Support Point | 3310 mm | 10'10" |
| Shipping Length | 7880 mm | 25'10" |
| Tail Swing Radius | 1750 mm | 5'9" |
| Counterweight Clearance | 1260 mm | 4'2" |
| Ground Clearance | 440 mm | 1'5" |
| Overall Undercarriage Length | 4870 mm | 16'0" |
| Wheel Base | 2550 mm | 8'4" |

| WORKING RANGES | | |
|-------------------------------------|--|-------|
| Boom | VA 5.2 m (17'1") | |
| Stick | 2.5 m (8'2") | |
| Bucket | GD 0.76 m ³ (0.99 yd ³) | |
| Maximum Loading Height | 7680 mm | 25'2" |
| Maximum Cutting Height | 10 410 mm | 34'2" |
| Maximum Digging Depth | 5580 mm | 18'4" |
| Maximum Reach at Ground Level | 8980 mm | 29'6" |
| Maximum Vertical Wall Digging Depth | 4580 mm | 15'0" |

| AIR CONDITIONING SYSTEM |
|---|
| The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 0.8 kg of refrigerant which has a CO ₂ equivalent of 1.144 metric tonnes. |

STANDARD & OPTIONAL EQUIPMENT

Standard and optional equipment may vary. Consult your Cat dealer for details.

| BOOM AND STICKS | STANDARD | OPTIONAL |
|---|----------|----------|
| 5.2 m (17'1") Variable Adjustable boom | • | |
| 2.2 m (7'3") stick | | • |
| 2.5 m (8'2") stick | | • |
| CAB | STANDARD | OPTIONAL |
| ROPS, sound suppression | • | |
| Deluxe cab | | • |
| Premium cab | | • |
| High-resolution 254 mm (10 in) LCD touchscreen monitor | • | |
| CAT TECHNOLOGY | STANDARD | OPTIONAL |
| Cat Product Link™ | • | |
| Remote Flash/Troubleshoot capability | • | |
| Cat Grade with 2D | | • |
| Cat Grade with Advanced 2D | | • |
| Cat Grade with 3D | | • |
| Cat Payload | | • |
| 2D E-Fence | | • |
| Laser Catcher | | • |
| ELECTRICAL SYSTEM | STANDARD | OPTIONAL |
| LED lights on chassis (left-hand, right-hand) and counterweight | • | |
| Programmable time-delay LED working lights | • | |
| Roading and indicator lights, front and rear | • | |
| Maintenance-free batteries | • | |
| Centralized electrical disconnect switch | • | |
| Electrical refueling pump | | • |
| ENGINE | STANDARD | OPTIONAL |
| Power mode selector | • | |
| One-touch low idle with auto engine speed control | • | |
| Auto engine idle shutdown | • | |
| 52°C (125°F) high-ambient cooling capacity | • | |
| -18°C (0°F) cold start capability | • | |
| Double element air filter with integrated precleaner | • | |
| Electric fuel priming pump | • | |

| HYDRAULIC SYSTEM | STANDARD | OPTIONAL |
|---|----------|----------|
| Automatic swing brake | • | |
| Auto hydraulic oil warm up | • | |
| Electronic main control valve | • | |
| Boom, stick, and bucket drift reduction valves | • | |
| 1-slider joysticks | • | |
| 2-slider joysticks | | • |
| Second high-pressure auxiliary circuit (one/two-way high-pressure flow) | | • |
| Medium pressure auxiliary circuit (one/two-way medium-pressure flow) | | • |
| Heavy lift mode | • | |
| Quick coupler circuit | | • |
| SmartBoom™ | | • |
| Ride control | | • |
| Cat tiltrotator support | | • |
| Joystick steering | | • |
| Separate dedicated swing pump | • | |
| SAFETY AND SECURITY | STANDARD | OPTIONAL |
| Rear- and right-side-view cameras | • | |
| 360° visibility | | • |
| Cat Asset Tracker | | • |
| Wide angle mirrors | • | |
| Ground-level engine shutoff switch | • | |
| Anti-skid plate and countersunk bolts on service platform | • | |
| Signaling/warning horn | | • |
| SERVICE AND MAINTENANCE | STANDARD | OPTIONAL |
| Sampling ports for Scheduled Oil Sampling (S·O·S SM) | • | |
| Automatic lubrication system for implement and swing system | | • |
| UNDERCARRIAGE AND STRUCTURES | STANDARD | OPTIONAL |
| 10.00-20 16 PR, dual tires | | • |
| 315/70R22.5, no gap dual tires | | • |
| 445/70R 19.5, single tires | | • |
| Automatic brake/axle lock | • | |
| 4000 kg (8,820 lb) counterweight | • | |
| All wheel drive | • | |
| Trailer package | | • |

Not all features are available in all regions. Please check with your local Cat dealer for specific offering availability in your area.
For additional information, refer to the Technical Specifications brochures for the M315 available at www.cat.com or your Cat dealer.

For more complete information on Cat products, dealer services and industry solutions, visit us on the web at www.cat.com.

© 2021 Caterpillar. All Rights Reserved.

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, Product Link, SmartBoom, S-O-S, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission. VisionLink is a trademark of VirtualSite Solutions LLC, registered in the United States and in other countries.

www.cat.com www.caterpillar.com

AEXQ3291-01
Replaces: AEXQ3291-00
Build Number: 07B
(Aus-NZ, Europe, N Am)

